INDUSTRIAL COMPONENT DATA

EM-2RPT/21AU-R/L-P 2909573 PHOENIX CONTACT Relay extension module for ELR-...-P hybrid motor starters, feedb..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EM-2RPT/21AU-R/L-P



Manufacturer	PHOENIX CONTACT
MPN / Reference	EM-2RPT/21AU-R/L-P
Catalog number	2909573
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-1E99C130C1
Generated	2026-11-19

Product Overview

Relay extension module for ELR-...-P hybrid motor starters, feedback of forward and reverse running when control signal is present, Push-in connection, DIN rail connector included
Expansion module relay for ELR-...-P hybrid motor starter, left and right drive response with control signal and push-in connection, rail bus connector included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2909573
Packing unit 1 pc
Catalog page Page 26 (C-5-2019)
GTIN 4055626445489
Weight per Piece (excluding packing) 180.000 g
Custom tariff number 85364190
Country of origin DE (Germany)
Drawings
Output data
Dimensions
Environmental Product Compliance

General
Connection data, output side
Standards and Regulations
Classifications
Drawings
Circuit diagram
Back to topGeneral
Mounting position Vertical (horizontal DIN rail)
Mounting type DIN rail mounting
Assembly instructions In rows with zero spacing
Ambient temperature (operation) -25 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Back to topOutput data
Contact type 1 PDT
Rated operating voltage Ue 24 V DC
230 V AC
Switching capacity according to IEC 60947-5-1 3 A (230 V, AC15)
2 A (24 V, DC13)
Back to topConnection data, output side
Connection name Load circuit
Connection method Push-in connection
Stripping length 10 mm
Conductor cross section solid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 14
Back to topDimensions
Width 22.50 mm
Height 106.60 mm
Depth 113.70 mm
Back to topStandards and Regulations
Standards/regulations IEC 60947-5-1
Back to topEnvironmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Back to topClassifications
eCl@ss
eCl@ss 5.0 27371600
eCl@ss 5.1 27371600
eCl@ss 6.0 2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EM-2RPT/21AU-R/L-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.