INDUSTRIAL COMPONENT DATA

D-UDK 4 BU 2775197 PHOENIX CONTACT End cover

Brand: PHOENIX CONTACT | Manufacturer Part Number: D-UDK 4 BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	D-UDK 4 BU
Catalog number	2775197
Category	Endplate and partition plate for terminal block
Minimum order	50 Pcs
Document ID	EO-5F550184AB
Generated	2026-11-18

Product Overview

End cover
End cap, length: 63.5 mm, width: 1.5 mm, height: 35.9 mm, colour: blue
End cover, depth: 35.9 mm, width: 1.5 mm, height: 63.5 mm, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type End cover
Data management status
Article revision 01
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (operation) 20 % ... 90 %
Permissible humidity (storage/transport) 30 % ... 70 %
Material specificationsColor blue (RAL 5015)
Flammability rating according to UL 94 V2
DimensionsWidth 1.5 mm

Height 63.5 mm
Depth 35.9 mm
Depth on NS 35/7,5 47 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / D-UDK 4 BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.