INDUSTRIAL COMPONENT DATA

D-UTTB 2,5/4 3047293 PHOENIX CONTACT End cover

Brand: PHOENIX CONTACT | Manufacturer Part Number: D-UTTB 2,5/4



Manufacturer	PHOENIX CONTACT
MPN / Reference	D-UTTB 2,5/4
Catalog number	D-UTTB 2,5/4
Category	Endplate and partition plate for terminal block
Minimum order	50 units
Document ID	EO-303FF1C3B9
Generated	2026-11-18

Product Overview

End cover
End cap, length: 69.9 mm, width: 2.2 mm, height: 57.5 mm, colour: grey
End cap, depth: 57.5 mm, width: 2.2 mm, height: 69.9 mm, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
End plate model (EF006586)	**Yes**
Partition model (EF006587)	**No**
Colour (EF000007)	**Grey**
Thickness (EF000125)	**2.2 mm**
Inflammability class of insulation material according to UL94 (EF002521)	**V0**

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3047293
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 219 (C-1-2017)
GTIN 4017918997267
Weight per Piece (excluding packing) 4.590 g

Custom tariff number 85389099
Country of origin DE (Germany)
General
Color gray
Material PA
Flammability rating according to UL 94 V0
Dimensions
Width 2.2 mm
Length 69.9 mm
Height 57.5 mm
General
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rai...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / D-UTTB 2,5/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.