INDUSTRIAL COMPONENT DATA

DS-ST 2,5 3036602 PHOENIX CONTACT Cover segment

Brand: PHOENIX CONTACT | Manufacturer Part Number: DS-ST 2,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	DS-ST 2,5
Catalog number	3036602
Category	Endplate and partition plate for terminal block
Minimum order	10 Pcs
Document ID	EO-6BFED3FD4D
Generated	2026-11-18

Product Overview

Cover segment

End caps for segments, large bus segment: 32.25 X 13.83 X 0.9, small bus segment: 22.65 X 11.65 X 0.9, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3036602
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 117 (C-3-2013)
GTIN 4017918607364
Weight per Piece (excluding packing) 0.870 g
Custom tariff number 85389099
Country of origin DE (Germany)
General
Color gray
Material PA
Flammability rating according to UL 94 V0
Dimensions
Min. material thickness 1 mm

Length 72 mm
Height 32.25 mm
General
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Standards and Regulations
Flammability rating according to UL 94 V0
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DS-ST 2,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.