INDUSTRIAL COMPONENT DATA

EO-E/UT/SH/LED/YE 1068076 PHOENIX CONTACT Socket, Pin connector pattern type E, for France and other countri..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-E/UT/SH/LED/YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-E/UT/SH/LED/YE
Catalog number	1068076
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-59A732367E
Generated	2026-11-18

Product Overview

Socket, Pin connector pattern type E, for France and other countries, with extended touch proofness/shutter, LED display, yellow, for mounting on a DIN rail in the service interface or direct mounting, 250 V AC, 16 A, -20 °C, 60 °C, NF C61-314 Power socket, Type E plug-in face, for France and other countries, with extended accidental contact protection/safety device, light indication, yellow, for rail mounting at the service interface or direct mounting, 250 VAC, 16 A, -20 °C, 60 °C, NFC61-314

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 1068076
Packing unit 1 pc
Minimum order quantity 5 pc
Catalog page Page 565 (C-3-2019)
GTIN 4055626738987
Weight per Piece (excluding packing) 72.000 g
Custom tariff number 85366990
Country of origin PL (Poland)
Drawings
Ambient conditions

Connection data
Classifications
Dimensions
General
Standards and Regulations
Drawings
Circuit diagram
Back to topDimensions
Width 45 mm
Height 75 mm
Depth 57.5 mm
Back to topAmbient conditions
Ambient temperature (operation) -20 °C ... 60 °C
Back to topGeneral
Nominal voltage UN 250 V AC (50 Hz)
Nominal current IN 16 A
Status display Yes
Contact material CuZn37
Color yellow
7042
Insulating material PA
Flammability rating according to UL 94 V0
Standards/regulations NF C61-314
Country ID France
Back to topConnection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
Back to topStandards and Regulations
Standards/regulations NF C61-314
Flammability rating according to UL 94 V0
Back to topClassifications
eCl@ss
eCl@ss 8.0 27142305
eCl@ss 9.0 27142305
Back to topETIM
ETIM 5.0 EC001663
ETIM 6.0 EC001663
ETIM 7.0 EC001663
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-E/UT/SH/LED/YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.