INDUSTRIAL COMPONENT DATA

EO-G/UT/SH/S 0804058 PHOENIX CONTACT Socket

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-G/UT/SH/S



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-G/UT/SH/S
Catalog number	0804058
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-DE8FB66017
Generated	2026-11-18

Product Overview

Socket
Power socket, Type G plug-in side, Screw connection, for Great Britain and other countries, with extended accidental contact protection/safety device, switch, grey, for rail mounting at service interface or direct mounting, 250 VAC, 13 A, -20 °C, 60 °C, BS1363-1/-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0804058
Packing unit 5 pc
Minimum order quantity 5 pc
Note Made to Order (non-returnable)
Catalog page Page 609 (C-3-2017)
GTIN 4055626225968
Weight per Piece (excluding packing) 9.990 g
Custom tariff number 85366990
Country of origin PL (Poland)
Dimensions
Width 45 mm
Height 75 mm

Depth 57.5 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 60 °C
General
Nominal voltage UN 250 V AC (50 Hz)
Nominal current IN 13 A
Status display No
Contact material CuZn37
Color gray
7042
Insulating material PA
Flammability rating according to UL 94 V0
Standards/regulations BS 1363-1/-2
Country ID Great Britain
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
Connection method Screw connection
Standards and Regulations
Standards/regulations BS 1363-1/-2
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127142300eCl@ss 6.027142300eCl@ss 7.027142305eCl@ss 8.027142305eCl@ss 9.027142305
ETIM 5.0EC001663ETIM 6.0EC001663

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-G/UT/SH/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.