INDUSTRIAL COMPONENT DATA

EO-I/UT/GN 0804088 PHOENIX CONTACT Prise, Modèle d'enfichage de type I, Raccordement vissé, pour la Chine / ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-I/UT/GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-I/UT/GN
Catalog number	0804088
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-FFCDBDCB23
Generated	2026-11-19

Product Overview

Prise, Modèle d'enfichage de type I, Raccordement vissé, pour la Chine / Australie et autres pays, vert, pour montage sur profilé dans une interface de service ou pour montage direct, 250 V AC, 10 A, -20 °C, 60 °C, GB 2009.1 et GB 1002
Power Outlet, Type I Plug-in Face, Screw Connection, for China/Australia and Other Countries, Green, for Rail Mounting at Service Interface or Direct Mounting, 250 VAC, 10 A, -20 °C, 60 °C, GB2009.1 and GB1002

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0804088
Packing unit 1
Catalog page Page 567 (C-3-2019)
GTIN 4055626226231
Custom tariff number 85366990
Dimensions
General
Standards and Regulations
Classifications
Ambient conditions
Connection data

Environmental Product Compliance
Dimensions
Width 45 mm
Height 75 mm
Depth 57.5 mm
Back to topAmbient conditions
Ambient temperature (operation) -20 °C ... 60 °C
Back to topGeneral
Nominal voltage UN 250 V AC (50 Hz)
Nominal current IN 10 A
Status display No
Contact material CuZn37
Color green
6021
Insulating material PA
Flammability rating according to UL 94 V0
Standards/regulations GB 2099.1 and GB 1002
Country ID China
Back to topConnection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
Connection method Screw connection
Back to topStandards and Regulations
Standards/regulations GB 2099.1 and GB 1002
Flammability rating according to UL 94 V0
Back to topEnvironmental Product Compliance
REACh SVHC
Lead 7439-92-1
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Back to topClassifications
eCl@ss
eCl@ss 4.0 27142300
eCl@ss 4.1 27142300
eCl@ss 5.0 27142300
eCl@ss 5.1 27142300
eCl@ss 6.0 27142300
eCl@ss 7.0 27142305
eCl@ss 8.0 27142305
eCl@ss 9.0 27142305
Back to topETIM
ETIM 5.0 EC00166...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-I/UT/GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.