INDUSTRIAL COMPONENT DATA

EO-L/PT/SH/GN 0804133 PHOENIX CONTACT Socket, Pin connector pattern type L, Push-in spring connection, for I..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-L/PT/SH/GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-L/PT/SH/GN
Catalog number	0804133
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-E1C8B4490A
Generated	2026-11-18

Product Overview

Socket, Pin connector pattern type L, Push-in spring connection, for Italy and other countries, with extended touch proofness/shutter, green, for mounting on a DIN rail in the service interface or direct mounting, 250 V AC, 16 A, -20 °C, 60 °C, CEI 23-50
Power socket, Plug-in face type L, Push-in spring connection, for Italy and other countries, with extended accidental contact protection/safety device, green, for rail mounting at the service interface or direct mounting, 250 VAC, 16 A, -20 °C, 60 °C, CEI23-50

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0804133
Packing unit 1
Catalog page Page 564 (C-3-2019)
GTIN 4055626226651
Custom tariff number 85366990
Drawings
Ambient conditions
Connection data
Environmental Product Compliance

Dimensions
General
Standards and Regulations
Classifications
Drawings
Circuit diagram
Back to topDimensions
Width 45 mm
Height 75 mm
Depth 57.5 mm
Back to topAmbient conditions
Ambient temperature (operation) -20 °C ... 60 °C
Back to topGeneral
Nominal voltage UN 250 V AC (50 Hz)
Nominal current IN 16 A
Status display No
Contact material CuZn37
Color green
6021
Insulating material PA
Flammability rating according to UL 94 V0
Standards/regulations CEI 23-50
Country ID Italy
Back to topConnection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
Connection method Push-in spring connection
Back to topStandards and Regulations
Standards/regulations CEI 23-50
Flammability rating according to UL 94 V0
Back to topEnvironmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Back to topClassifications
eCl@ss
eCl@ss 4.0 27142300
eCl@ss 4.1 27142300
eCl@ss 5.0 27142300
eCl@ss 5.1 27142300
eCl@ss 6.0 27142300
eCl@ss 7.0 27142305
eCl@ss 8.0 27142305
eCl@ss 9.0 27142305

Back to topETIM
ETIM 5.0 EC0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-L/PT/SH/GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.