INDUSTRIAL COMPONENT DATA

PTTB 4-HESILED 24 (5X20) 3211888 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTTB 4-HESILED 24 (5X20)



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTTB 4-HESILED 24 (5X20)
Catalog number	3211888
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-BFBBF3403A
Generated	2026-11-19

Product Overview

Fuse modular terminal block
Rail terminal for fuse, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 24 V, nominal current: 28 A, connection type: Push-in connection, 1st floor, Sizing section: 4 mm², cross-section: 0.2 mm²- 6 mm², connection type: Push-in connection, 2. Floor, Sizing cross-section: 4 mm², cross-section: 0.2 mm²- 6 mm², Mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3211888
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 95 (C-1-2017)
GTIN 4055626380568
Weight per Piece (excluding packing) 24.240 g
Custom tariff number 85369095
Country of origin CN (China)
General
Note The current is determined by the fuse used, the voltage by the light indicator.

Number of levels 2
Number of connections 4
Nominal cross section 4 mm²
Color black
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 1.02 W
Fuse G / 5 x 20
Fuse type Glass / ceramics / ...
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation max. 1.6 W (With single arrangement of the fuse terminal block in the event of overload)
max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)
max. 4 W (With single arrangement of the fuse terminal block in the event of a short-circuit)
max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)
LED voltage range 12 V AC/DC ... 30 V AC/DC
LED current range 0.31 mA ... 0.95 mA
Connection in acc. with standard IEC 60947-7-1
Maximum load current 32 A
Nominal current IN 28 A
Nominal voltage UN 500 V
Connection in acc. with standard IEC 60947-7-3
Maximum load current (upper level) 6.3 A (the current is determined by the fuse used)
Nominal current IN(upper level) 6.3 A
Nominal voltage UN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTTB 4-HESILED 24 (5X20) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.