

INDUSTRIAL COMPONENT DATA

FL MEM PLUG/MRM 2891275 PHOENIX CONTACT

Configuration memory

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL MEM PLUG/MRM



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL MEM PLUG/MRM
Catalog number	2891275
Category	PLC memory card
Minimum order	1 Pcs
Document ID	EO-98A1A2182D
Generated	2026-09-21

Product Overview

Configuration memory

Interchangeable device setting memory for easy replacement and commissioning of the device. In addition, the license for Redundant Media Management (MRM) is saved, for use within the Media Redundancy Protocol (MRP)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > I/O**

Additional Product Information

Key Commercial Data

Orderkey 2891275

Packing unit 1 pc

Catalog page Page 423 (C-6-2017)

GTIN 4046356165433

Weight per Piece (excluding packing) 19.000 g

Custom tariff number 84717098

Country of origin DE (Germany)

Dimensions

Width 16 mm

Height 49 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) 0 °C ... 55 °C (non-condensing)

Ambient temperature (storage/transport) -20 °C ... 70 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)

Function

Basic functions Configuration memory and manager for the media redundancy protocol (MRP)

General

Mounting type In the host system

Type AX Fine granularity

Net weight 19 g

Conformity with EMC directives

Developed in acc. with standard IEC 61000-6.2

Test standard IEC 61000-4-2 (ESD)

Test result Criterion B

Test standard IEC 61000-4-3 (immunity to radiated interference)

Test result Criterion A

Test standard IEC 61000-4-4 (burst)

Test result Criterion A

Test standard IEC 61000-4-5 (surge)

Test result Criterion A

Test standard IEC 61000-4-6 (immunity to conducted interference)

Test result Criterion A

Test standard IEC 61000-4-8 (immunity to magnetic fields)

Test result Criterion A

Test standard EN 55022 (emitted interference)

Test result Criterion A

Standards and Regulations

Electromagnetic compatibility Conformance with EMC Directive 2004/108/EC

Noise emission EN 61000-6-3/-4

Noise immunity EN 61000-6-2:2005

Environmental Produc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL MEM PLUG/MRM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.