

INDUSTRIAL COMPONENT DATA

FA MCR-EX-HT-TS-I-OLP 1105681 PHOENIX CONTACT Ex i-Output loop-powered head transmitter for transmitting up ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FA MCR-EX-HT-TS-I-OLP

PRODUCT IMAGE\n\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	FA MCR-EX-HT-TS-I-OLP
Catalog number	1105681
Category	Temperature transformer
Minimum order	1 Pcs
Document ID	EO-B812FC1954
Generated	2026-09-21

Product Overview

Ex i-Output loop-powered head transmitter for transmitting up to 2 sensor signals from RTD and CT sensors, as well as resistance and voltage transmitters using 4 mA... 20 mA. HART, Standard Configuration, Safety Integrity Level (SIL, IEC 61508): 2, Systematic Capability: 3, Screw Connection

Head transmitter powered in output loop to transmit up to two thermoresistance and TC sensor signals, as well as resistance and voltage transmitters via HART or 4 mA ... 20 mA, freely configurable, SIL 2/3, intrinsic safety, screw connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FA MCR-EX-HT-TS-I-OLP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.