INDUSTRIAL COMPONENT DATA

BMK 20X 8 WH CUS 0824231 PHOENIX CONTACT Fabric label sheet

Brand: PHOENIX CONTACT | Manufacturer Part Number: BMK 20X 8 WH CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	BMK 20X 8 WH CUS
Catalog number	0824231
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-2DA91EACD7
Generated	2026-11-18

Product Overview

Fabric label sheet
Fabric label sheet, available: Elbow, white, labeled according to customer's instructions, mounting class: glued, usable surface: 20 mm x 8 mm, Number of individual indices: 270

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0824231
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 293 (C-5-2013)
GTIN 4046356351096
Weight per Piece (excluding packing) 9.000 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 8 mm
Width (a) 20 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 80 °C
General
Color white
Base element material Polyester foil
Components Silicone-free
Flammability rating according to UL 94 V0
Material Polyester foil
Number of individual labels 270
Adhesive Acrylic
Printability Plotter
Device 5144615 CMS-P1-PLOTTER
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type adhesive
Standards and Regulations
Flammability rating according to UL 94 V0
Classifications
eCl@ss 10.0.127400629eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027141137eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss 7.027141137eCl@ss 8.027141137eCl@ss 9.027400629
ETIM....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BMK 20X 8 WH CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.