INDUSTRIAL COMPONENT DATA

MINI MCR-2-FM-RC-PT 2904508 PHOENIX CONTACT Monitoring module

Brand: PHOENIX CONTACT | Manufacturer Part Number: MINI MCR-2-FM-RC-PT



Manufacturer	PHOENIX CONTACT
MPN / Reference	MINI MCR-2-FM-RC-PT
Catalog number	2904508
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-BD58906B24
Generated	2026-11-18

Product Overview

Monitoring module
Fault monitoring module with plug-in connection technology to evaluate and report collective fault monitoring system errors and to monitor supply voltages. Error signaling using an NC contact. Push-in connection technology, standard configuration

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2904508
Packing unit 1 pc
Catalog page Page 104 (C-5-2017)
GTIN 4046356857390
Weight per Piece (excluding packing) 96.300 g
Custom tariff number 85437090
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 6.2 mm
Height 110.5 mm

Depth 120.5 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Input data
Description of the input Voltage input for redundancy monitoring
Number of inputs 1
Voltage input signal 9.9 V DC ... 30 V DC
Output data
Number of outputs 1
Voltage output signal 9.6 V DC ... 29.7 V DC
Max. output current 3.2 A
Switching output
Output name Switching output
Maximum switching voltage 30 V DC
Max. switching current 50 mA
Power supply
Supply voltage range 12 V DC ... 24 V DC -20 % ... +25 % (The DIN rail bus connector (ME 6,2 TBUS-2 1,5/5-ST-3,81 GN, Order No. 2869728) can be used to bridge the supply voltage. It can be snapped onto a 35 mm DIN rail according to EN 60715))
Max. current consumption < 16 mA (at 24 V DC)
Power consumption < 410 mW (at 24 V DC)
Connection data
Connection method Push-in connection
Single conductor/terminal point, solid, with ferrule, min. 0.14 mm²
Single conductor/terminal point, solid, with ferrule, max. 2.5 mm²
Single conductor/terminal point, solid, without ferrule, min. 0.14 mm²
Single conductor/terminal point, solid, without ferr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MINI MCR-2-FM-RC-PT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.