INDUSTRIAL COMPONENT DATA

FBP-3/4SL 1030010 PHOENIX CONTACT Cover profile, length: 65 mm, width: 74.1 mm, height: 32 mm, color: transp..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FBP-3/4SL



Manufacturer	PHOENIX CONTACT
MPN / Reference	FBP-3/4SL
Catalog number	1030010
Category	Test plug for terminal blocks
Minimum order	1 Pcs
Document ID	EO-30E6B8336F
Generated	2026-11-19

Product Overview

Cover profile, length: 65 mm, width: 74.1 mm, height: 32 mm, color: transparent
Blind cap, number of poles: 4, color: transparent
Blind plug, number of positions: 4, color: transparent

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Technical dataProduct propertiesProduct type Blind plug
Number of positions 4
Data management status
Article revision 00
DimensionsWidth 74.1 mm
Height 65 mm
Depth 32 mm
Material specificationsColor transparent
Flammability rating according to UL 94 V0
Insulating material PVC
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (storage/transport) 30 % ... 70 %

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FBP-3/4SL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.