INDUSTRIAL COMPONENT DATA

DFLK-D37 SUB/S 2280336 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFLK-D37 SUB/S



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFLK-D37 SUB/S
Catalog number	2280336
Category	Interface module
Minimum order	5 Pcs
Document ID	EO-5187904F6F
Generated	2026-11-18

Product Overview

Interface module
The VARIOFACE feed-through module makes a 1:1 connection between screw connection terminals and a subminiature D-plug (no. 37). A separate mass shunt is available.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2280336
Packing unit 5 pc
Catalog page Page 575 (C-5-2017)
GTIN 4017918054441
Weight per Piece (excluding packing) 94.200 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Width 39 mm
Height 128.4 mm
Depth 33 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 25 V AC
60 V DC
Max. perm. current (per branch) 2.5 A
Max. permissible current (all branches) 50 A
Number of positions 37
Mounting position any
Assembly instructions In rows with zero spacing
Degree of protection IP20
Connection data for connection 1
Connection name Field level
Connection in acc. with standard IEC / EN
Connection method Screw connection
Stripping length 8 mm
Screw thread M3
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method D-SUB pin strip
Number of positions 37
Standards and Regulations
Connection in acc. with standard CUL
Standards/regulations IEC 60664
DIN EN 50178
Rated insulation voltage 125 V
Rated surge voltage 1.2 kV (Functional insulation)
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declarat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFLK-D37 SUB/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.