INDUSTRIAL COMPONENT DATA

DFK 5-9,5 0706605 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK 5-9,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK 5-9,5
Catalog number	0706605
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-1D3EB87D0D
Generated	2026-11-18

Product Overview

Panel feed-through terminal block
Terminal block, connection type: Screw connection with traction capsule, Weld/flat socket connection, number of poles: 1, charging current: 18 A, cross-section: 0.2 mm² - 6 mm², connection direction of the conductor with respect to the plug direction: 90 °, width: 38 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 0706605
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 641 (C-1-2013)
GTIN 4017918003777
Weight per Piece (excluding packing) 5.200 g
Custom tariff number 85369010
Country of origin BG (Bulgaria)
General
Number of levels 1
Number of connections 2

Nominal cross section 1.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V2
Maximum load current 17.5 A
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current IN 17.5 A
Maximum load current 17.5 A
Nominal voltage UN 690 V
Open side panel No
Number of positions 1
Dimensions
Width 9.5 mm
Length 38.6 mm
Pitch 10 mm
Plate thickness 0.5 mm ... 3.5 mm
Connection data
Connection side Level 1 ext. 1
Connection method Screw connection
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 6 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 4 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 10
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²
2 conductors with same cross section, solid min. 0.2 mm²
2 conduct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK 5-9,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.