
INDUSTRIAL COMPONENT DATA

ST 1,5 BK 3037067 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST 1,5 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST 1,5 BK
Catalog number	3037067
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-B60D2652B0
Generated	2026-11-18

Product Overview

Feed-through terminal block
Feed-through terminal, nominal voltage: 500 V, nominal current: 17.5 A, number of connections: 2, connection type: Spring connection, 1st floor, Dimensioning cross-section: 1.5 mm², cross-section: 0.08 mm² - 1.5 mm², mounting class: NS 35/7.5, NS 35/15, colour: black
Feed-through terminal block, nom. voltage: 500 V, nominal current: 17.5 A, number of connections: 2, connection method: Spring-cage connection, 1 level, Rated cross section: 1.5 mm2, cross section: 0.08 mm2 - 1.5 mm2, mounting type: NS 35/7,5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Feed-through terminal block
Number of connections 2
Number of rows 1
Potentials 1
Data management status
Article revision 11
Insulation characteristics
Overvoltage category III
Degree of pollution 3

Electrical propertiesRated surge voltage 6 kV
Maximum power dissipation for nominal condition 0.56 W
Connection dataNumber of connections per level 2
Nominal cross section 1.5 mm²
1 level
Stripping length 8 mm ... 10 mm
Internal cylindrical gage A1
Connection in acc. with standard IEC 60947-7-1
Conductor cross section rigid 0.08 mm² ... 1.5 mm²
Cross section AWG 28 ... 16 (converted acc. to IEC)
Conductor cross section flexible 0.08 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG] 28 ... 16 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 1.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 1.5 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm²
Nominal current 17.5 A
Maximum load current 17.5 A (with 1.5 mm² conductor cross section)
Nominal voltage 500 V
Nominal cross section 1.5 mm²
Ex dataRated data (ATEX/IECEx)
Identification ? II 2 GD Ex eb IIC Gb
Operating temperature range -60 °C ... 110 °C
Ex-certified accessories 3030417 D-ST 2,5
3030721 ATP-ST 4
1204504 SZF 0-0,4X2,5
3022276 CLIPFIX 35-5
3022218 CLIPFIX 35
List of bridges Plug-in bridge / FBS 2-4 / 3030116
Plug-in bridge / FBS 3-4 / 303...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST 1,5 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.