INDUSTRIAL COMPONENT DATA

ST 4-HEDI 3035140 PHOENIX CONTACT Lever-type disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST 4-HEDI



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST 4-HEDI
Catalog number	3035140
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-154F34664A
Generated	2026-11-18

Product Overview

Lever-type disconnect terminal block
Lever-interruptible terminal block, nominal voltage: 500 V, nominal current: 20 A, connection type: Spring connection, Dimensioning cross-section: 4 mm², cross-section: 0.08 mm² - 6 mm², mounting: NS 35/7.5, NS 35/15, colour: black/orange
Lever-type disconnect terminal block, nom. voltage: 500 V, nominal current: 20 A, connection method: Spring-cage connection, Rated cross section: 4 mm2, cross section: 0.08 mm2 - 6 mm2, mounting: NS 35/7,5, NS 35/15, color: black/orange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Disconnect terminal block
Area of application Railway industry
Machine building
Plant engineering
Number of connections 2
Number of rows 1
Potentials 1
Data management status
Article revision 06
Insulation characteristics

Overvoltage category III
Degree of pollution 3
Electrical propertiesRated surge voltage 6 kV
Maximum power dissipation for nominal condition 1.02 W
Connection dataNumber of connections per level 2
Nominal cross section 4 mm²
Level 1
Stripping length 8 mm ... 10 mm
Internal cylindrical gage A4
Connection in acc. with standard IEC 60947-7-1
Conductor cross section rigid 0.08 mm² ... 6 mm²
Cross section AWG 28 ... 10 (converted acc. to IEC)
Conductor cross section flexible 0.08 mm² ... 4 mm²
Conductor cross section, flexible [AWG] 28 ... 12 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 4 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 4 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1 mm²
Nominal current 20 A (with 6 mm² conductor cross section)
Maximum load current 20 A (with 6 mm² conductor cross section)
Nominal voltage 500 V
Nominal cross section 4 mm²
DimensionsWidth 6.2 mm
Height 61.5 mm
Depth on NS 35/7,5 62.5 mm
Depth on NS 35/15 70 mm
Material specificationsColor multicolored
black (RAL 9005)
orange (RAL 2003)
Flammability rating according to UL 94 V0
Insulating...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST 4-HEDI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.