
INDUSTRIAL COMPONENT DATA

STTB 2,5-L/N 3036330 PHOENIX CONTACT Double-level spring-cage terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: STTB 2,5-L/N



Manufacturer	PHOENIX CONTACT
MPN / Reference	STTB 2,5-L/N
Catalog number	3036330
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-E757BA26FD
Generated	2026-11-18

Product Overview

Double-level spring-cage terminal block
Double-deck spring terminal block, nominal voltage: 500 V, nominal current: 22 A, connection type: Spring connection, 1st and 2nd floor, Sizing cross-section: 2.5 mm², cross-section: 0.08 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3036330
Packing unit 50 pc
Catalog page Page 158 (C-1-2017)
GTIN 4017918823139
Weight per Piece (excluding packing) 9.900 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Number of levels 2
Number of connections 4
Nominal cross section 2.5 mm²

Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Connection in acc. with standard IEC 60947-7-1
Nominal current IN 22 A
Maximum load current 26 A (with 4 mm² conductor cross section)
Nominal voltage UN 500 V
Open side panel Yes
Relative insulation material temperature index (Elec.; UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STTB 2,5-L/N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.