INDUSTRIAL COMPONENT DATA

UHK 4-FS(8-2,8-0,8) 2017237 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UHK 4-FS(8-2,8-0,8)



Manufacturer	PHOENIX CONTACT
MPN / Reference	UHK 4-FS(8-2,8-0,8)
Catalog number	2017237
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-D9DC9BCD7E
Generated	2026-11-18

Product Overview

Feed-through terminal block
Feed-through terminal, nominal voltage: 800 V, nominal current: 32 A, 1st floor, left-hand connection, connection type: Screw connection, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 4 mm², connection type: Flat plug connection, mounting: NS 35/7.5, NS 35/15, NS 32, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 2017237
Packing unit 50 pc
Catalog page Page 499 (C-1-2017)
GTIN 4017918052690
Weight per Piece (excluding packing) 10.900 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 1
Number of connections 2
Nominal cross section 4 mm²

Color gray
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W
Connection method Screw connection
Maximum load current 40 A (with 4 mm² conductor cross section)
Nominal current IN 32 A
Nominal voltage UN 800 V
Connection method Slip-on connection
Open side panel Yes
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire pro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UHK 4-FS(8-2,8-0,8) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.