INDUSTRIAL COMPONENT DATA

A 2,5 7 3200289 PHOENIX CONTACT Ferrule A 2,5 7

Brand: PHOENIX CONTACT | Manufacturer Part Number: A 2,5-7



Manufacturer	PHOENIX CONTACT
MPN / Reference	A 2,5-7
Catalog number	3200289
Category	Cable end sleeve
Minimum order	1000 Pcs
Document ID	EO-476A019D0B
Generated	2026-11-18

Product Overview

Ferrule A 2,5 7
Toe cap, length: 7 mm, color: silver
Ferrule, sleeve length: 7 mm, color: silver

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Ferrules

Additional Product Information

Technical dataProduct propertiesProduct type Cable end sleeve
Conductor category stranded conductors, class 2, 5, 6 / B, C, K, M
Data management status
Article revision 05
Connection dataConductor connection
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG max. 14
Stripping length 7 mm
DimensionsDimensional drawing
Sleeve length 7 mm
Length contact range 7 mm
Maximum stripping length 7 mm
Ferrule diameter 2.2 mm
Sleeve wall thickness 0.15 mm

Inner dimensions of the insulating collar 3.4 mm
Material specificationsColor silver-colored
Material CU-DHP
Coating tin-plated (galvanic)
Surface characteristics Tin-plated
Mechanical propertiesTechnical data
Sleeve length 7 mm
Environmental and real-life conditionsAmbient conditions
Permanent temperature 105 °C
Short-term temperature 120 °C
Standards and regulationsDesign according to standard DIN 46228-1, UL 486F-A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / A 2,5-7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.