INDUSTRIAL COMPONENT DATA

A 4 -18 3202834 PHOENIX CONTACT Ferrule

Brand: PHOENIX CONTACT | Manufacturer Part Number: A 4-18



Manufacturer	PHOENIX CONTACT
MPN / Reference	A 4-18
Catalog number	3202834
Category	Cable end sleeve
Minimum order	1000 Pcs
Document ID	EO-C8F3F2D9EA
Generated	2026-11-18

Product Overview

Ferrule
Toe cap, length: 18 mm, colour: silver
Ferrule, sleeve length: 18 mm, color: silver

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Ferrules

Additional Product Information

Technical dataProduct propertiesProduct type Cable end sleeve
Conductor category stranded conductors, class 2, 5, 6 / B, C, K, M
Data management status
Article revision 05
Connection dataConductor connection
Conductor cross section flexible max. 4 mm²
Conductor cross section AWG max. 12
Stripping length 18 mm
DimensionsDimensional drawing
Sleeve length 18 mm
Length contact range 18 mm
Maximum stripping length 18 mm
Ferrule diameter 2.8 mm
Sleeve wall thickness 0.2 mm

Inner dimensions of the insulating collar 4 mm
Material specificationsColor silver-colored
Material CU-DHP
Coating tin-plated (galvanic)
Surface characteristics Tin-plated
Mechanical propertiesTechnical data
Sleeve length 18 mm
Environmental and real-life conditionsAmbient conditions
Permanent temperature 105 °C
Short-term temperature 120 °C
Standards and regulationsDesign according to standard DIN 46228-1, UL 486F-A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / A 4-18 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.