INDUSTRIAL COMPONENT DATA

# AI 0,75- 6 WH 3201314 PHOENIX CONTACT Ferrule

**Brand: PHOENIX CONTACT | Manufacturer Part Number: AI 0,75-6 WH**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | AI 0,75-6 WH |
| Catalog number | 3201314 |
| Category | Cable end sleeve |
| Minimum order | 100 Pcs |
| Document ID | EO-8C75251022 |
| Generated | 2026-11-18 |

## Product Overview

Ferrule
Toe cap, cuff length: 6 mm, length: 12 mm, color: white
Ferrule, sleeve length: 12 mm, color: white

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Ferrules |

## Additional Product Information

Technical dataProduct propertiesProduct type Cable end sleeve
Conductor category stranded conductors, class 2, 5, 6 / B, C, K, M
Data management status
Article revision 06
Connection dataConductor connection
Conductor cross section flexible max. 0.75 mm²
Conductor cross section AWG max. 18
Stripping length 9 mm
DimensionsDimensional drawing
Sleeve length 12 mm
Length contact range 6 mm
Maximum stripping length 9 mm
Ferrule diameter 1.3 mm
Sleeve wall thickness 0.15 mm

Insulating collar thickness 0.25 mm
Inner dimensions of the insulating collar 2.8 mm
Material specificationsColor white (RAL 9010)
Material CU-DHP
Flammability rating according to UL 94 HB
Coating tin-plated (galvanic)
Surface characteristics Tin-plated
Components free from silicone and halogen
Mechanical propertiesTechnical data
Sleeve length 12 mm
Environmental and real-life conditionsAmbient conditions
Permanent temperature 105 °C (-40 °C no load / 0 °C dynamic load)
Short-term temperature 120 °C
Standards and regulationsDesign according to standard UL 486F-E, Sonderfarbe

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AI 0,75-6 WH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.