

INDUSTRIAL COMPONENT DATA

FFKDSA1/ V-2,54- 6 BD:X8 1010562 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 160 V, p..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FFKDSA1/ V-2,54- 6 BD:X8

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	FFKDSA1/ V-2,54- 6 BD:X8
Catalog number	1010562
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-DF1A055DBD
Generated	2026-09-29

Product Overview

Terminal for printed circuit board, rated voltage: 160 V, pitch: 2.54 mm, number of poles: 6, type of connection: spring clamp push-in, mounting: Soldering by wave, color: green

Terminal block for printed circuit board, nominal current: 6 A, dimensioning voltage (III/2): 160 V, nominal section: 0.5 mm², Number of potentials: 6, Number of rows: 1, Number of poles per row: 6, family of articles: FFKDS(A) 0.5/.. -V, pitch: 2.54mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 90°, color: green, Pin arrangement: Double linear pin arrangement, Pin length [P]: 3.5mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FFKDSA1/ V-2,54- 6 BD:X8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.