INDUSTRIAL COMPONENT DATA

# GMSTB 2,5/ 2-ST-7,62CPBDS2/X14 1713462 PHOENIX CONTACT Plug

**Brand: PHOENIX CONTACT | Manufacturer Part Number: GMSTB 2,5/ 2-ST-7,62CPBDS2/X14**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | GMSTB 2,5/ 2-ST-7,62CPBDS2/X14 |
| Catalog number | 1713462 |
| Category | Cable connector |
| Minimum order | 50 Pcs |
| Document ID | EO-6301C64313 |
| Generated | 2026-11-19 |

## Product Overview

Plug
Connector for printed circuit board, nominal section: 2.5 mm², color: green, rated current: 12 A, sizing voltage (III/2): 630 V, surface contacts: Tin, contact type: Connection female, Number of potentials: 2, Number of rows: 1, Number of poles per row: 2, number of connections: 2, article family: GMSTB 2.5/.. -ST, pitch: 7.62 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: 0 °,Stecksystem: CLASSIC COMBICON, Lock: without, type of packaging: boxed packaging

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 1713462
Packing unit 1
GTIN 4055626372396
Custom tariff number 85366990
Dimensions
Length [ l ] 18.2 mm
Width [ w ] 13.24 mm
Height [ h ] 15 mm
Pitch 7.62 mm

Dimension a 7.62 mm
General
Range of articles GMSTB 2,5/..-ST
Number of positions 2
Connection method Screw connection with tension sleeve
Insulating material group I
Rated voltage (III/2) 630 V
Nominal current IN 12 A
Nominal cross section 2.5 mm²
Flammability rating according to UL 94 V0
Screw thread M3
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309
ETIM 5.0EC002638ETIM 6.0EC002638

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / GMSTB 2,5/ 2-ST-7,62CPBDS2/X14 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.