INDUSTRIAL COMPONENT DATA

FTP-2/2 SERVICE 3069464 PHOENIX CONTACT Test plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: FTP-2/2 SERVICE



Manufacturer	PHOENIX CONTACT
MPN / Reference	FTP-2/2 SERVICE
Catalog number	3069464
Category	Test plug for terminal blocks
Minimum order	1 Pcs
Document ID	EO-99191AD07E
Generated	2026-11-19

Product Overview

Test plug
Test connector, nominal voltage: 400 V, nominal current: 24 A, Dimensioning cross-section: 2.5 mm², colour: red
Test plug, nom. voltage: 400 V, nominal current: 24 A, Rated cross section: 2.5 mm2, color: red

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Technical dataProduct propertiesProduct type Test plug terminal block
Number of positions 2
Pitch 8.2 mm
Number of connections 4
Number of rows 1
Potentials 2
Data management status
Article revision 02
Insulation characteristics
Overvoltage category III
Electrical propertiesRated surge voltage 4 kV
Maximum power dissipation for nominal condition 1.31 W
Test surge voltage 5 kV
Connection dataNominal cross section 6 mm²

Test socket torque 0.5
Note The conductor cross section depends on the cable lug used
Conductor cross section flexible 0.5 mm² ... 2.5 mm²
Conductor cross section, flexible [AWG] 20 ... 14 (converted acc. to IEC)
Nominal current 24 A
Maximum load current 24 A
Nominal voltage 400 V AC/DC
Nominal cross section 2.5 mm²
DimensionsWidth 19.5 mm
Height 86 mm
Pitch 8.2 mm
Material specificationsColor red (RAL 3001)
Flammability rating according to UL 94 V0
Insulating material group I
Insulating material PA
Mechanical propertiesMechanical data
Open side panel No
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (storage/transport) 30 % ... 70 %
MountingMounting type Insertion in base strip

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FTP-2/2 SERVICE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.