
INDUSTRIAL COMPONENT DATA

FK-MCP 1,5/ 2-ST-3,5GYAUBD7,8Q 1848419 PHOENIX CONTACT Connector for printed circuit board, nominal current:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MCP 1,5/ 2-ST-3,5GYAUBD7,8Q



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MCP 1,5/ 2-ST-3,5GYAUBD7,8Q
Catalog number	1848419
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-CBCE80FD7C
Generated	2026-11-18

Product Overview

Connector for printed circuit board, nominal current: 8 A, number of poles: 2, pitch: 3.5 mm, connection type: spring clamp push-in, color: gray, surface, contacts: Gold
Connector for printed circuit board, nominal section: 1.5 mm², color: gray, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: FK-MCP 1.5/.. -ST, pitch: 3.5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataItem PropertiesProduct Type Printed Circuit Board Connector
Product Family FK-MCP 1.5/.. -ST
Product Line COMBICON Connectors S
Number of poles 2
Step 3.5 mm
Number of connections 2
Number of rows 1

Number of potentials 2
Clamping flange without
Data Maintenance Status
Article Review 00
Electrical PropertiesNominal Current IN 8 A
Nominal voltage UN 160 V
Contact resistance 1.6 m?
Sizing voltage (III/3) 160 V
Dimensioning transient voltage (III/3) 2.5 kV
Dimensioning voltage (III/2) 160 V
Dimensioning Transient Voltage (III/2) 2.5 kV
Nominal voltage (II/2) 320 V
Dimensioning transient voltage (II/2) 2.5 kV
Connection dataConnection technology
Connector System COMBICON MC 1.5
Nominal Section 1.5 mm²
Contact Connection Type Female
Blockade
Locking system without
Clamping flange without
Connecting Conductors
Connection type Push-in spring connection
Connection Direction Driver/PCB 0 °
Rigid conductor section 0.14 mm² ... 1.5 mm²
Flexible conductor section 0.14 mm² ... 1.5 mm²
AWG Conductor Section 26 ... 16
Flexible conductor section with toe cap, without plastic sleeve 0.25 mm² ... 1.5 mm²
Flexible conductor section with toe cap, with plastic sleeve 0.25 mm² ... 0.5 mm²
Male gauge a x b / Diameter 2.4 mm x 1.5 mm / -
Peel Length 9 mm
Facts about toe caps without an insulated collar
Recommended crimp pliers 1212034 CRIMPFOX 6
toe caps without insulating collar, according to DIN 46228-1 Cross-section: 0.25 mm²; Length: 7 mm
Cross-section: 0.34 mm²; Length: 7 mm
Cros...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MCP 1,5/ 2-ST-3,5GYAUBD7,8Q with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.