INDUSTRIAL COMPONENT DATA

FKC 2,5/12-ST-5,08 BD:12-1SO 1752641 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKC 2,5/12-ST-5,08 BD:12-1SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKC 2,5/12-ST-5,08 BD:12-1SO
Catalog number	1752641
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-E8EE87B7DC
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, article family: FKC 2.5/.. -ST, pitch: 5.08 mm, connection type: Push-in spring connection, conductor connection/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1752641
Packing unit 50 pc
Minimum order quantity 50 pc
GTIN 4046356321273
Weight per Piece (excluding packing) 21.590 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Length [l] 25.73 mm

Width [w] 61.58 mm
Height [h] 15 mm
Pitch 5.08 mm
Dimension a 55.88 mm
General
Range of articles FKC 2,5/..-ST
Number of positions 12
Connection method Push-in spring connection
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 320 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 630 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 2.5 mm²
Internal cylindrical gage A2
Stripping length 10 mm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²
2 conductors with same cross section, stranded, TWIN fer...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKC 2,5/12-ST-5,08 BD:12-1SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.