INDUSTRIAL COMPONENT DATA

FKC 2,5/ 3-STF-5,08 PA1,3 1093325 PHOENIX CONTACT Connector for printed circuit board, nominal current: 12 A..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKC 2,5/ 3-STF-5,08 PA1,3

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	FKC 2,5/ 3-STF-5,08 PA1,3
Catalog number	1093325
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-091C39AC29
Generated	2026-11-19

Product Overview

Connector for printed circuit board, nominal current: 12 A, number of poles: 3, pitch: 5,08 mm, connection type: spring clamp push-in, color: green, surface contacts: Tin
Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Female connection, number of rows: 1, number of poles: 3, article family: FKC 2.5/.. -STF, pitch: 5.08 mm, connection type: Push-in spring connection, conductor connection direction/printed circuit board: 0 °, Clamping hook: - Clamping hook, plug-in system: CLASSIC COMBICON, Locking: Screw locking, fixing type: Air clamping (screw), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKC 2,5/ 3-STF-5,08 PA1,3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.