INDUSTRIAL COMPONENT DATA

FKC 2,5/ 4-ST-5,08-RF BD:-GND 1706047 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKC 2,5/ 4-ST-5,08-RF BD:-GND



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKC 2,5/ 4-ST-5,08-RF BD:-GND
Catalog number	1706047
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-FE3C1C4581
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: FKC 2.5/.. -ST-RF, pitch: 5.08 mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: Snap locking, fixing type: Socket flange, packaging type: boxed
Printed circuit board connector, nominal section: 2.5 mm2, color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Sn, contact connection type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, article family: FKC 2.5/.. -ST-RF, pitch: 5.08 mm, connection type: Push-in spring connection, conductor connection direction/printed circuit board: 0°, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: Snap locking, fixing type: Locking trigger, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Plug component, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 4, pitch: 5.08 mm, connection method: Push-in spring connection, color: green, contact surface: Tin
Your advantages
Time saving push-in connection, tools not requiredIntuitive use through colour coded actuation leverQuick and convenient testing using integrated test optionCan be combined with the MSTB 2´,5 rangeIntuitive locking mechanism prevents

accidental disconnectionKey Commercial Data
Orderkey 1706047
Packing unit 1
GTIN 4046356836456
Custom tariff number 85366990
General
Range of articles FKC 2,5/..-ST-RF
Type of contact Female connector
Number of positions 4
Connection method Push-in spring connection
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 320 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 630 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 2.5 mm²
Internal cylindrical gage A2
Stripping length 10 mm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKC 2,5/ 4-ST-5,08-RF BD:-GND with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.