
INDUSTRIAL COMPONENT DATA

FKC 2,5/ 6-ST-5,08 BKBDWH:BR- 1047116 PHOENIX CONTACT Connector for printed circuit board, number of poles: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKC 2,5/ 6-ST-5,08 BKBDWH:BR-



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKC 2,5/ 6-ST-5,08 BKBDWH:BR-
Catalog number	1047116
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-A3B3C7504E
Generated	2026-11-19

Product Overview

Connector for printed circuit board, number of poles: 3, pitch: 5,08 mm, color: black
PCB connector, nominal cross-section: 2.5 mm², colour: black, nominal current: 12 A, nominal voltage (III/2): 320 V, surface contacts: Tin, contact type: Female, number of rows: 1, number of poles: 3, article family: FKC 2.5/.. -ST, pitch: 5.08mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, attachment type: without, packing type: boxed packaging
PCB connector, nominal cross section: 2.5 mm2, color: black, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Socket, number of rows: 1, number of positions: 3, product range: FKC 2,5/..-ST, pitch: 5.08 mm, connection method: Push-in spring connection, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct type PCB connector
Product family FKC 2,5/..-ST
Product line COMBICON Connectors M
Number of positions 3

Pitch 5.08 mm
Number of rows 1
Data management status
Article revision 02
Electrical propertiesNominal current IN 12 A
Nominal voltage UN 320 V
Contact resistance 1 m?
Rated voltage (III/3) 320 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 320 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 630 V
Rated surge voltage (II/2) 4 kV
Connection dataConnection technology
Connector system COMBICON MSTB 2,5
Nominal cross section 2.5 mm²
Contact connection type Socket
Interlock
Locking type without
Mounting flange without
Conductor connection
Connection method Push-in spring connection
Connection direction of the conductor to plug-in direction 0 °
Conductor/PCB connection direction 0 °
Conductor cross section rigid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1.5 mm²
Cylindrical gauge a x b / diameter 2.8 mm x 2.0 mm / 2.4 mm
Stripping length 10 mm
Specifications for ferrules without insulating collar
recommended crimping tool 1212034 CRIMPFOX 6
ferrules without insulating collar,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKC 2,5/ 6-ST-5,08 BKBDWH:BR- with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.