INDUSTRIAL COMPONENT DATA

FKCN 2,5/ 3-ST-5,08BD24-22 SO 1003382 PHOENIX CONTACT Connector for printed circuit board, number of poles: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKCN 2,5/ 3-ST-5,08BD24-22 SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKCN 2,5/ 3-ST-5,08BD24-22 SO
Catalog number	1003382
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-D3F934B03E
Generated	2026-11-19

Product Overview

Connector for printed circuit board, number of poles: 3, pitch: 5,08 mm, connection type: spring clamp push-in, color: green, surface contacts: Tin
Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: FKCN 2.5/.. -ST, pitch: 5.08 mm, connection type: Push-in spring connection, conductor connection/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

PCB connector, nominal current: 12 A, test voltage (III/2): 320 V, number of positions: 3, pitch: 5.08 mm, connection type: Push-in spring connection, color: green, contact surface: Tin
Business data
Order Code 1003382
Packaging quantity (VPE) 50 Items
Minimum Order Quantity 50 Items
Note On-demand production (no pick-up)
GTIN 4055626471709
Weight per unit (excluding packaging) 3,700 GRM

Customs Duty Number 85366990
Country of origin BG (Bulgaria)
Measurements
Measurements [l] 27.1 mm
Width [w] 15 mm
Height [h] 10.9 mm
Pitch Measurement 5.08 mm
Measure to 10 mm
General
Product Family FKCN 2.5/.. -ST
Number of poles 3
Connection type Push-in connection by spring
Nominal track gauge 2.5 mm²
Environmental Product Compliance
China RoHS Period for intended use: unlimited = EFUP-e
No hazardous substances above the limit values
Classifications
eCl@ss
eCl@ss 5.1 27260700
eCl@ss 6.0 27260700
eCl@ss 7.0 27440309
eCl@ss 8.0 27440309
eCl@ss 9.0 27440309
ETIM
ETIM 5.0 EC002638
ETIM 6.0 EC002638
ETIM 7.0 EC002638

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKCN 2,5/ 3-ST-5,08BD24-22 SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.