

INDUSTRIAL COMPONENT DATA

FKDSO 2,5 HV/3-R7,5KMGYTP11-13 1656012 PHOENIX CONTACT Printed circuit board terminal, rated current: 24 A, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKDSO 2,5 HV/3-R7,5KMGYTP11-13

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	FKDSO 2,5 HV/3-R7,5KMGYTP11-13
Catalog number	1656012
Category	Printed circuit board terminal
Minimum order	100 Pcs
Document ID	EO-C06AE19EE0
Generated	2026-09-29

Product Overview

Printed circuit board terminal, rated current: 24 A, rated voltage (III/2): 630 V, rated cross-section: 2.5 mm², number of potentials: 3, number of rows: 1, number of poles per row: 3, article family: FKDSO 2.5 HV/.. -R, pitch: 7.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: light gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.53 mm, number of solder pins per potential: 1. Printed variant, item with side pin output on the right

Terminal block for printed circuit board

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKDSO 2,5 HV/3-R7,5KMGYTP11-13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.