INDUSTRIAL COMPONENT DATA

FL NAT 2008 2702881 PHOENIX CONTACT Managed NAT Switch 2000, 8 RJ45 ports 10/100 Mbps, degree of protection:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL NAT 2008



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL NAT 2008
Catalog number	2702881
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-00E8EF082F
Generated	2026-11-19

Product Overview

Managed NAT Switch 2000, 8 RJ45 ports 10/100 Mbps, degree of protection: IP20, PROFINET Conformance-Class A, 1:1-NAT, Virtual NAT, IP-Masquerading
Managed NAT Switch 2000, 8 RJ45 ports 10/100 MBit/s, PROFINET Conformance-Class A, 1:1-NAT, Virtual NAT, IP-Masquerading

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data
Orderkey 2702881
Packing unit 1 pc
Catalog page Page 328 (C-6-2019)
GTIN 4055626376622
Weight per Piece (excluding packing) 380.000 g
Custom tariff number 85176200
Country of origin DE (Germany)
Note
Ambient conditions
Function
Supply voltage

Connection data
Environmental Product Compliance
Dimensions
Interfaces
Network expansion parameters
General
Standards and Regulations
Classifications
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Back to topDimensions
Width 45 mm
Height 130 mm
Depth 115 mm
Back to topAmbient conditions
Degree of protection IP20
Ambient temperature (operation) 0 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Permissible humidity (operation) 10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)
Air pressure (operation) 86 kPa ... 108 kPa (1500 m above sea level)
Air pressure (storage/transport) 86 kPa ... 108 kPa
Back to topInterfaces
Interface Ethernet (RJ45)
No. of ports 8 (RJ45 ports)
Note on the connection method Auto negotiation and autocrossing
Transmission physics Copper
Transmission speed 10/100 Mbps
Transmission length 100 m (per segment)
Signal LEDs Data receive, link status
Back to topFunction
Basic functions Router for standard routing, NAT, 1:1-NAT and port forwarding
Management Web-based management (HTTP/HTTPS)
SNMPv1/v2/v3
Command-line interface (Telnet, SSH)
Diagnostic functions RMON History
L...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL NAT 2008 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.