INDUSTRIAL COMPONENT DATA

FL SWITCH 1000T-2POE-GT-2SFP 1026765 PHOENIX CONTACT Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 1000T-2POE-GT-2SFP



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 1000T-2POE-GT-2SFP
Catalog number	1026765
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-144ED3CFC7
Generated	2026-11-19

Product Overview

Industrial Ethernet Switch
Unmanaged PoE Switches 1000, 2 SFP Ports 100/1000 MBit/s, 2 RJ45 Ports 10/100/1000 MBit/s

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data
Orderkey 1026765
Packing unit 1 pc
GTIN 4055626519463
Weight per Piece (excluding packing) 569.300 g
Custom tariff number 85176200
Country of origin TW (Taiwan)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 42.8 mm
Height 100 mm
Depth 101 mm
Ambient conditions

Degree of protection IP30
Ambient temperature (operation) -40 °C ... 75 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Permissible humidity (operation) 5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)
Air pressure (operation) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)
Air pressure (storage/transport) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)
Interfaces
Interface 2 Fiber optic interface
No. of ports 2 (SFP ports)
Transmission physics Depending on the SFP module
Transmission speed 100/1000 Mbps (full duplex)
Transmission length up to 80 km (Depending on the fiber/SFP module used)
Interface 3 Ethernet (PoE)
No. of ports 2 (RJ45 ports)
Connection method RJ45 socket
Transmission physics Ethernet RJ45
Transmission speed 10/100/1000 Mbps
Transmission length 100 m (Between transmitter / receiver)
Signal LEDs LNK/ACT, POE
Function
Basic functions Store-and-forward switch, 10/100/1000 Mbps, auto negotiation, redundant power supply, PoE according to IEEE 802.3at/802.3af, jumbo frames up to 10240 bytes, alarm contact
Additional functions Autonegotiat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 1000T-2POE-GT-2SFP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.