INDUSTRIAL COMPONENT DATA

FL SWITCH 1001T-4POE-GT-SFP 1026932 PHOENIX CONTACT Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 1001T-4POE-GT-SFP



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 1001T-4POE-GT-SFP
Catalog number	1026932
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-E6D1A4B6B6
Generated	2026-11-18

Product Overview

Industrial Ethernet Switch
Unmanaged PoE Switches 1000, 1 RJ45 Port 10/100/1000 MBit/s, 1 SFP Port 1000 MBit/s, 4 RJ45 Ports 10/100/1000 MBit/s

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data
Orderkey 1026932
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4055626520346
Weight per Piece (excluding packing) 492.000 g
Custom tariff number 85176200
Country of origin TW (Taiwan)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 30 mm
Height 149 mm

Depth 107.8 mm
Ambient conditions
Degree of protection IP30
Ambient temperature (operation) -40 °C ... 75 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Permissible humidity (operation) 5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)
Air pressure (operation) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)
Air pressure (storage/transport) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)
Interfaces
Interface 1 Ethernet
No. of ports 1 (RJ45 ports)
Transmission physics Ethernet RJ45
Transmission speed 10/100/1000 Mbps
Transmission length 100 m (Between transmitter / receiver)
Signal LEDs LNK/ACT, POE
Interface 2 Fiber optic interface
No. of ports 1 (SFP ports)
Transmission physics Depending on the SFP module
Transmission speed 1000 Mbps (full duplex)
Transmission length up to 80 km (Depending on the fiber/SFP module used)
Interface 3 Ethernet (PoE)
No. of ports 4 (RJ45 ports)
Connection method RJ45 socket
Transmission physics Ethernet RJ45
Transmission speed 10/100/1000 Mbps
Transmission length 100 m (Between transmitter / receiver)
Signal LEDs LNK/AC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 1001T-4POE-GT-SFP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.