INDUSTRIAL COMPONENT DATA

FL SWITCH 1104NT-SFP 1343023 PHOENIX CONTACT Narrow Ethernet switch, wide temperature range, four RJ45 ports..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 1104NT-SFP



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 1104NT-SFP
Catalog number	1343023
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-EE0D9A867B
Generated	2026-11-18

Product Overview

Narrow Ethernet switch, wide temperature range, four RJ45 ports, one SFP port, 10/100/1000 Mbit/s on all ports, automatic transmission rate detection, autocrossing function and QoS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Technical dataDimensionsWidth 22.5 mm
Height 123 mm
Depth 90 mm
NotesRestriction of Use
EMC Indication EMC: Class A product, see manufacturer's statement in the download center
Material DataShell material Fiber-reinforced polycarbonate
Aluminum/Sheet Steel DC01
assemblyType of mounting Rail mounting
InterfacesEthernet (RJ45)
Number of interfaces 4
Connection type RJ45
Note about the connection type Autonegoation and Autocrossing
Transmission speed 10/100/1000 MBit/s
Transmission Physics Ethernet on RJ45-twisted pair

Transmission Length 100 m (per segment)
Signal LEDs Data Receiving, Link Status
Number of channels 4 (RJ45 ports)
Ethernet (SFP)
Number of interfaces 1
Connection type SFP
Transmission speed 100/1000 MBit/s (duplex)
Transmission Physics Depending on the SFP module
Transmission Length up to 40 km (depending on the fiber/SFP module used)
Signal LEDs Data Receiving, Link Status
Number of channels 1 (SFP port)
Item PropertiesProduct Type Switch
Product Family Unmanaged Switch 1000
MTTF 87.5 Years (MIL-HDBK-217F Standard, Temperature 25°C, 100% Operating Cycle)
1071.9 Years (SN 29500 standard, temperature 25 °C, duty cycle 21%)
839.8 Years (Telcordia Standard, temperature 25°C, duty cycle 21% (5 days per week, 8 hours per day))
Switch Functions
Basic Functionality Unmanaged Switch
Autonegotiation
Store-and-Forward-Switching-Mode
MAC Address Table 4K
Status and Diagnostic Indications LEDs: Us, liaison and activity by port
Other Functions 100 BASE-TX/100BASE-FX (IEEE 80...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 1104NT-SFP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.