INDUSTRIAL COMPONENT DATA

FL SWITCH 4000T-8POE-2SFP 1026923 PHOENIX CONTACT Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH 4000T-8POE-2SFP



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH 4000T-8POE-2SFP
Catalog number	1026923
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-EBE772B79E
Generated	2026-11-18

Product Overview

Industrial Ethernet Switch
Managed PoE Switches 4000, 2 SFP Ports 100/1000 MBit/s, 8 RJ45 Ports 10/100 MBit/s

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data
Orderkey 1026923
Packing unit 1 pc
GTIN 4055626519555
Weight per Piece (excluding packing) 1,612.000 g
Custom tariff number 85176200
Country of origin TW (Taiwan)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 75 mm
Height 170 mm
Depth 152 mm
Ambient conditions

Degree of protection IP30
Ambient temperature (operation) -40 °C ... 75 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Permissible humidity (operation) 5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)
Air pressure (operation) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)
Air pressure (storage/transport) 57 kPa ... 108 kPa (up to 4850 m above mean sea level)
Interfaces
Interface 2 Fiber optic interface
No. of ports 2 (SFP ports)
Transmission physics Depending on the SFP module
Transmission speed 100/1000 Mbps (full duplex)
Transmission length up to 80 km (Depending on the fiber/SFP module used)
Interface 3 Ethernet (PoE)
No. of ports 8 (RJ45 ports)
Connection method RJ45
Note on the connection method Auto negotiation and autocrossing
Transmission physics Ethernet in RJ45 twisted pair
Transmission speed 10/100 Mbps
Transmission length 100 m
Function
Basic functions Store and forward switch, Extended Ring and IEEE redundancy, Multicast control, IGMP snooping, trunking, Port and Tagging VLANs, Port and IEEE 802.1x security, SNMP V3 and Https security, SNTP,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH 4000T-8POE-2SFP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.