INDUSTRIAL COMPONENT DATA

C-SCM 2,5/6,3X0,8 3240162 PHOENIX CONTACT Connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: C-SCM 2,5/6,3X0,8



Manufacturer	PHOENIX CONTACT
MPN / Reference	C-SCM 2,5/6,3X0,8
Catalog number	3240162
Category	Crimp splices for copper conductor
Minimum order	100 Pcs
Document ID	EO-8523B34782
Generated	2026-11-18

Product Overview

Connector
Flat, uninsulated connector, 1.5 - 2.5 mm², 6.3 x 0.8
Flat connector, non-insulated, 1.5 - 2.5 mm2, 6.3 x 0.8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > TOOL fox

Additional Product Information

Technical dataProduct propertiesProduct type Connector
Data management status
Article revision 00
Electrical propertiesFuse DIN 46248
DimensionsDimensional drawing
Width 6.3 mm
Sleeve length 20 mm
Maximum stripping length 8 mm
Min. material thickness 0.8 mm
Material specificationsColor silver-colored
Material Brass
Coating tin-plated
Insulating material nicht zutreffend
Mechanical propertiesTechnical data

Sleeve length 20 mm

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) 110 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C-SCM 2,5/6,3X0,8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.