

INDUSTRIAL COMPONENT DATA

UK 6-FSI/C-LED24 3001938 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 6-FSI/C-LED24



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 6-FSI/C-LED24
Catalog number	3001938
Category	Fuse terminal block
Minimum order	1 Pcs
Document ID	EO-5F315DB0C1
Generated	2026-09-23

Product Overview

Fuse modular terminal block

Terminal block for flat fuse, cross-section: 0.2-6 mm², AWG: 26-8, width: 8.2 mm, colour: Black, with light indication, light indicator voltage: 24 V DC, light indication current: 2 mA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3001938

Packing unit 50 pc

Catalog page Page 461 (C-1-2017)

GTIN 4017918100971

Weight per Piece (excluding packing) 21.120 g

Custom tariff number 85369010

Country of origin TR (Turkey)

General

Number of levels 1

Number of connections 2

Mounting type NS 35/7,5

Color black

Number of positions 1
Insulating material PA
Flammability rating according to UL 94 V0
Electrical data
Fuse C
Fuse type Flat
Degree of pollution 3
Insulating material group I
Connection in acc. with standard IEC 60947-7-3
Maximum current with single arrangement 30 A (special arrangements on request)
Voltage LED LED red
Current LED 2 mA (LED red)
Dimensions
Width 8.2 mm
Height NS 35/7,5 52 mm
Height NS 35/15 59.5 mm
Height NS 32 57 mm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 10 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 6 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 8
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 6 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 2.5 mm²
2 conductors with same cross section, stranded min. 0.2 mm²....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 6-FSI/C-LED24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.