INDUSTRIAL COMPONENT DATA

FLKM 14/8P/HF/PLC 2295680 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM 14/8P/HF/PLC

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM 14/8P/HF/PLC
Catalog number	2295680
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-AD30DC7430
Generated	2026-11-18

Product Overview

Interface module
VARIOFACE interconnect module, for 8 channels with an additional terminal block for each signal, for a common positive potential, halogen-free

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2295680
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4017918429638
Weight per Piece (excluding packing) 124.450 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Width 56.3 mm
Height 77 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 60 °C

General
Max. perm. operating voltage 60 V AC/DC
Max. perm. current (per branch) 1 A
Max. permissible current (all branches) 3 A (for plus and minus)
Mounting position any
Degree of protection IP00
Connection data for connection 1
Connection name Control side
Connection in acc. with standard IEC 60603-13
Connection method FLK14 pin strip
Number of positions 14
Connection data for connection 2
Connection name Field level
Connection method Screw connection
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Number of positions 20
Standards and Regulations
Designation Air clearances and creepage distances
Standards/regulations DIN EN 50178: 1998-04
Rated insulation voltage 63 V
Rated surge voltage 0.6 kV (1.2/50 us)
Insulation Functional insulation
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM 14/8P/HF/PLC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.