INDUSTRIAL COMPONENT DATA

FLKM-2KS40/PMT/YCS 2321907 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM-2KS40/PMT/YCS



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM-2KS40/PMT/YCS
Catalog number	2321907
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-B269E2DE6A
Generated	2026-11-18

Product Overview

Passive module
VARIOFACE interconnection module for analog components, 8 channels, redundant connector. For Yokogawa CENTUM CS3000 AAI135, AAI835 cards.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2321907
Packing unit 1
GTIN 4046356599917
Custom tariff number 85369010
Dimensions
Width 135 mm
Height 77 mm
Depth 58 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General

Max. perm. operating voltage < 60 V DC
< 50 V AC
Max. perm. current (per branch) 1 A
Mounting position any
Assembly instructions In rows with zero spacing
Degree of protection IP20
Connection data for connection 1
Connection name Field level
Connection method Screw connection
Stripping length 8 mm
Screw thread M3
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method Yokogawa KS-compatible
Torque 0.5 Nm
Number of connections 2
Number of positions 40
Supported controller
Controller YOKOGAWA CS3000 CentumVP
- suitable I/O card AAI135
AAI835
Controller YOKOGAWA STARDOM
- suitable I/O card NFAI135
NFAI835
Standards and Regulations
Designation Air clearances and creepage distances
Standards/regulations EN 50178
Rated insulation voltage 63 V
Rated surge voltage 0.6 kV (basic insulation)
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM-2KS40/PMT/YCS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.