
INDUSTRIAL COMPONENT DATA

FLKM-2KS40/SPT/CS/C-L 2321855 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM-2KS40/SPT/CS/C-L



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM-2KS40/SPT/CS/C-L
Catalog number	2321855
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-07DFE2BE74
Generated	2026-11-18

Product Overview

Passive module
Interconnect module for Yokogawa AAV 141, AAV 142, AAT 141, AAI 141, AAI 143, AAV 542, AAI 543, AAI 841, AAB 841, AAI 135, AAP 135, AAI 835 and AAR 181 analog I/O modules. Redundant system connection, on the field side with spring connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2321855
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356350648
Weight per Piece (excluding packing) 337.000 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Width 194.5 mm
Height 126 mm
Depth 40 mm

Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 24 V DC ±10 %
Max. perm. current (per branch) 1 A
Mounting position any
Assembly instructions In rows with zero spacing
Connection data for connection 1
Connection name Field level
Connection method Spring-cage connection
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method Yokogawa KS-compatible
Torque 0.5 Nm
Number of connections 1
Number of positions 40
Note Usable system cables: Phoenix Contact YUC40, Yokogawa KS1
Supported controller
Controller YOKOGAWA CS3000 CentumVP
- suitable I/O card AAI543
AAI141
AAI143
AAI835
AAI841
AAI135
AAR181
AAT141
AAV141
AAV142
AAB841
AAV542
Controller YOKOGAWA STARDOM
- suitable I/O card NFAI141
NFAI43
NFAI543
NFAI135
NFAP135
NFAV141
NFAV142
NFAV542
NFAB841
NFAI841
NFAI835

Standards and Regulations
Standards/regulations DIN EN 50178
Rated surge voltage 0.8 kV
Degree of pollution 2
Overvoltage category III
Environmental Product Compliance
REACh SVHC....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM-2KS40/SPT/CS/C-L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.