INDUSTRIAL COMPONENT DATA

FLKM-2KS50/BFI/SPT/CS/C-L 2321842 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM-2KS50/BFI/SPT/CS/C-L



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM-2KS50/BFI/SPT/CS/C-L
Catalog number	2321842
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-97E3DF0B73
Generated	2026-11-18

Product Overview

Passive module
Interconnect module for Yokogawa ADV 151, ADV 161, ADV 551 and ADV 561 I/O cards with one fuse (5 x 20) and fuse fault indication (LED) per channel. Redundant system connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2321842
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356350631
Weight per Piece (excluding packing) 800.000 g
Custom tariff number 85369010
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 344 mm
Height 126 mm

Depth 70 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Note Voltage monitoring on the module does not work in combination with upstream HESILED fuse terminal blocks with integrated LED display.
Do not connect adjacent channels to SELV/ PELV and voltages dangerous to the touch.
No additional touch protection is required when using a SELV/PELV voltage (<= 25 V AC or 60 V DC).
Against adjacent modules in the support rail direction at least one functional insulation on the output-side is complied with. If the application has higher requirements on the insulation (basic insulation or reinforced insulation), then these must be realized through suitable measures (e. g. partition plates).
Max. perm. operating voltage 24 V DC
Nominal voltage UN 19.2 V DC ... 26.4 V DC
Max. perm. current (per branch) 100 mA (observe derating)
Max. permissible current (all branches) 4 A (observe derating)
Status display LED red
Mounting position any
Assembly instructions In rows with zero spacing
Output data
Designation
Contact type 1 N/O contact
Type of switch c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM-2KS50/BFI/SPT/CS/C-L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.