INDUSTRIAL COMPONENT DATA

FLKM-2KS50/PMT/ADV151/YCS 2321884 PHOENIX CONTACT Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM-2KS50/PMT/ADV151/YCS



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM-2KS50/PMT/ADV151/YCS
Catalog number	2321884
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-77FEFCBA77
Generated	2026-11-18

Product Overview

Passive module
VARIOFACE input module with screw connection, 32 channels, redundant connection connector for Yokogawa ADV151, ADV161 input cards.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2321884
Packing unit 1 pc
Note Made to Order (non-returnable)
GTIN 4046356563703
Weight per Piece (excluding packing) 643.000 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Width 232 mm
Height 111 mm
Depth 68 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 70 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Note Voltage monitoring on the module does not work in combination with upstream HESILED fuse terminal blocks with integrated LED display.
Max. perm. operating voltage 24 V DC
Max. perm. current (per branch) 63 mA AC (protected by fuse, observe derating)
Max. permissible current (all branches) 2 A (protected by fuse, observe derating)
Mounting position any
Assembly instructions In rows with zero spacing
Degree of protection IP00
Connection data for connection 1
Connection name Field level
Connection method Screw connection
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Number of connections 1
Number of positions 64
Connection data for connection 2
Connection name Controller level
Connection method Yokogawa KS-compatible
Torque 0.5 Nm
Number of connections 2
Number of positions 50
Note Usable system cables: Phoenix Contact YUC50, Yokogawa AKB331
Standards and Regulations
Designation Air clearances and creepage distances between the power circuits
Standards/regulations DIN EN 50178
Rated insul...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM-2KS50/PMT/ADV151/YCS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.