
INDUSTRIAL COMPONENT DATA

FLKM-D50 SUB/S 2281157 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM-D50 SUB/S



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM-D50 SUB/S
Catalog number	2281157
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-4D3DD069CB
Generated	2026-11-19

Product Overview

Interface module
VARIOFACE module, with screw connection and subminiature plug D, for mounting on NS 35/7.5 or NS 32, number of poles 50

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2281157
Packing unit 5 pc
Note Made to Order (non-returnable)
Catalog page Page 225 (IF-2002)
GTIN 4017918054601
Weight per Piece (excluding packing) 236.100 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Width 112.5 mm
Height 77 mm
Depth 58.5 mm

Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 25 V AC
60 V DC
Max. perm. current (per branch) 2.5 A
1.5 A (with even load on all branches)
Number of positions 50
Mounting position any
Degree of protection IP20
Connection data for connection 1
Connection name Field level
Connection in acc. with standard IEC / EN
Connection method Screw connection
Stripping length 8 mm
Screw thread M3
Conductor cross section solid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Standards and Regulations
Connection in acc. with standard CUL
Standards/regulations IEC 60664
IEC 60664A
DIN VDE 0110
DIN VDE 0160 (in parts)
Rated insulation voltage 125 V
Rated surge voltage 1.2 kV (Functional insulation)
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM-D50 SUB/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.