
INDUSTRIAL COMPONENT DATA

FLKMS-D37 SUB/B/ZFK3DS/PE 2295952 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKMS-D37 SUB/B/ZFK3DS/PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKMS-D37 SUB/B/ZFK3DS/PE
Catalog number	2295952
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-36D3FE6AA5
Generated	2026-11-18

Product Overview

Interface module
VARIOFACE module, with spring-loaded terminal connection and subminiature female connector D, for mounting on NS 35/7.5 or NS 32, number of poles 37

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2295952
Packing unit 1 pc
GTIN 4017918448035
Weight per Piece (excluding packing) 137.320 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Width 75 mm
Height 90 mm
Depth 70 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C

General
Max. perm. operating voltage 25 V AC (60 V DC)
Max. perm. current (per branch) 2.5 A
Number of positions 37
Status display No
Mounting position any
Degree of protection IP00
Connection data for connection 1
Connection name Field level
Connection in acc. with standard IEC / EN
Connection method Spring-cage connection
Stripping length 7 mm
Conductor cross section solid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 1.5 mm²
Conductor cross section AWG 24 ... 14
Number of positions 39
Connection data for connection 2
Connection name Controller level
Connection method D-SUB socket strip
Number of positions 37
Standards and Regulations
Connection in acc. with standard CUL
Designation Air clearances and creepage distances
Standards/regulations DIN EN 50178: 1998-04
Rated insulation voltage 125 V
Rated surge voltage 1.2 kV (1.2/50 us)
Insulation Functional insulation
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKMS-D37 SUB/B/ZFK3DS/PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.