INDUSTRIAL COMPONENT DATA

SACC-CI-M12FSS-4CON-L180 THR PE 1406409 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CI-M12FSS-4CON-L180 THR PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CI-M12FSS-4CON-L180 THR PE
Catalog number	1406409
Category	Contact insert for circular connectors
Minimum order	20 Pcs
Document ID	EO-911B18E780
Generated	2026-11-18

Product Overview

Flush-type connector
Plug-in Mounting Connector, Universal, 4-Pole, Female Connection, Straight, M12, Coding: S, Printed Circuit Board Mounting, THR Solder Connection, RoHS II Alternative Product Without Exception 6c (Pb< 0.1%) Item Code: 1238743
Contact holder, Universal, 4-pole, Female connection, straight, M12, coding: S, Printed circuit board mounting, THR solder connection, Alternative product according to RoHS II without exception 6c (Pb < 0.1%) item code: 1238743

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1406409
Packing unit 20 pc
Minimum order quantity 20 pc
Note Made to Order (non-returnable)
Catalog page Page 288 (C-2-2013)
GTIN 4046356804349
Weight per Piece (excluding packing) 4.200 g
Custom tariff number 85366990
Country of origin DE (Germany)
Ambient conditions

Ambient temperature (operation) -25 °C ... 105 °C
-40 °C ... 105 °C (without mechanical actuation)
Degree of protection IP67 (correctly plugged in and locked)
General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 12 A
Rated voltage 630 V
Rated surge voltage 6 kV
Number of positions 4
Insulation resistance >= 100 M?
Coding S power
Standards/regulations M12 connector
Signal type/category Universal
Overvoltage category III
Degree of pollution 3
Connection method THR solder connection
Insertion/withdrawal cycles > 100
Mounting type PCB mounting
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA4T
Cable
Standards/specifications M12 connector
Standards and Regulations
Standard designation M12 connector
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CI-M12FSS-4CON-L180 THR PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.