INDUSTRIAL COMPONENT DATA

SACC-E-MINMS-5CON-PG13/0,5 1521452 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-E-MINMS-5CON-PG13/0,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-E-MINMS-5CON-PG13/0,5
Catalog number	1521452
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-760CE38D9E
Generated	2026-11-18

Product Overview

Flush-type connector
Conn. plug. Incorp. e.g. sensors/actuators, 5 poles, 7/8", front wall c. Pg13.5 thread, w. braid wire. PVC 0.5 m, 5 x 0.75 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1521452
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 49 (C-4-2015)
GTIN 4017918949679
Weight per Piece (excluding packing) 52.100 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Length of cable 0.5 m
Ambient conditions
Ambient temperature (operation) -40 °C ... 85 °C (Plug)
Degree of protection IP67

General
Rated current at 40°C 9 A
Rated voltage 250 V
Number of positions 5
Insulation resistance >= 100 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Individual wires
Mounting type Front mounting Pg13.5
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Au
Contact carrier material PUR
Material, knurls Zinc die-cast, nickel-plated
Sealing material Viton
Cable
Cable type PVC litz wire
Conductor cross section 0.75 mm²
AWG signal line 18
Conductor structure signal line 24x 0.20 mm
Core diameter including insulation 2.7 mm
Thickness, insulation 0.85 mm (Core insulation)
Wire colors brown, white, blue, black, green-yellow
Material conductor insulation PE
Standards and Regulations
Connection in acc. with standard CUL
Flammability rating according to UL 94 HB
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 25;
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.027140815eC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-E-MINMS-5CON-PG13/0,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.