INDUSTRIAL COMPONENT DATA

RC-07P1N8A6300 1594449 PHOENIX CONTACT Device connector with Pg13.5 screw-in thread, straight, shielded: yes..

Brand: PHOENIX CONTACT | Manufacturer Part Number: RC-07P1N8A6300



Manufacturer	PHOENIX CONTACT
MPN / Reference	RC-07P1N8A6300
Catalog number	1594449
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-C689BDC957
Generated	2026-11-19

Product Overview

Device connector with Pg13.5 screw-in thread, straight, shielded: yes, Screw locking, M23, No. of pos.: 7, type of contact: Pin, Crimp connection, Axial O-ring, Central fixing, Panel thickness min.: 1 mm, Panel thickness max.: 4.5 mm
M23, Conect. plug. to be apar. front wall, RC, straight, shielded: yes, Screw lock, No. of poles: 7, Direction of rotation: Standard, contact type: Male, Crimped connection, Axial O-ring, Central fixing, Min. wall thickness: 1 mm, Max. wall thickness: 4.5 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1240497

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1594449
Packing unit 1
GTIN 4046356201438
Custom tariff number 85366990
Data of the insulating body
Note Order information: Order crimp contacts Ø 2 mm separately
Coding N
Contact connection method Crimp connection

Type of contacts Pin
Application Signal
Number of positions 7
Contact diameter of power contacts 2 mm
Nominal current per power contact at 25°C 20 A
Nominal voltage, power contact 300 V
Rated surge voltage 2.5 kV
Overvoltage category II
Degree of pollution 3
Overvoltage category II
Degree of pollution 3
Housing data
Housing material Metal
Type of locking Screw locking
Degree of protection (when plugged in) IP67
Thread type M23
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260701eCl@ss 6.027260708eCl@ss 7.027440312eCl@ss 8.027440103eCl@ss 9.027440102
ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC001121ETIM 6.0EC001121
UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNSPSC 12.0143201404UNSPSC 13.239121413

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RC-07P1N8A6300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.